

FE1.1

USB 2.0 HIGH SPEED 4-PORT HUB CONTROLLER

Product Brief



INTRODUCTION

The FE1.1 is a highly integrated, high quality, high performance, low power consumption, yet low cost solution for USB 2.0 High Speed 4-Port Hub.

It adopts Multiple Transaction Translator (MTT) architecture to explore the maximum possible throughput. Six, instead of two, non-periodic transaction buffers are used to minimize potential traffic jamming. The whole design is based on state-machine-control to reduce the response delay time; no micro controller is used in this chip.

To guarantee high quality, the whole chip is covered by *Test Scan Chain* – even on the high speed (480MHz) modules, so that all the logic components could be fully tested before shipping. Special Build-In-Self-Test mode is designed to exercise all high, full, and low speed Analog Front End (AFE) components on the packaging and testing stages as well.

Low power consumption is achieved by using 0.18 μ m technology and comprehensive power/clock control mechanism. Most part of the chip will not be clocked unless needed.

FEATURES

- Fully compliant with Universal Serial Bus Specification Revision 2.0 (USB 2.0);
 - Upstream facing port supports High-Speed (480MHz) and Full-Speed (12MHz) modes;
 - 4 downstream facing ports support High-Speed (480MHz), Full-Speed (12MHz), and Low-Speed (1.5MHz) modes;
- Integrated USB 2.0 Transceivers;
- Integrated upstream 1.5K Ω pull-up, downstream 15K Ω pull-down, and serial resistors;
- Integrated 5V to 3.3V and 1.8V regulator.
- Integrated Power-On-Reset circuit;
- Integrated 12MHz Oscillator with feedback resistor, and crystal load capacitance;
- Integrated 12MHz-to-480MHz Phase Lock Loop (PLL);
- *Multiple Transaction Translators* (MTT) –
 - One TT for each downstream port;
 - Alternate Interface 0 for Single-TT, and Alternate Interface 1 for Multiple-TT;
 - Each TT could handle 64 periodic Start-Split transactions, 32 periodic Complete-Split transactions, and 6 none-periodic transactions;
- Automatic self-power status monitoring;



- Automatic re-enumeration when Self-Powered switching to Bus-Powered;
- Board configured options –
 - Ganged or Individual Power Control Mode* select;
 - Global or Individual Over-Current Detection Mode* select;
 - Removable or Non-Removable Downstream Devices* configuration;
- Comprehensive Port Indicators support:
 - Standard downstream port status indicators (Green and Amber LED control for each downstream port);
 - Hub active LED support;

Terminus Technology Inc.
5F., No.9, Ln.130, Sec.3, Minsheng E.Rd.,
Songshan Dist., Taipei City, Taiwan
www.terminus.com.tw